AMENDMENTS TO THE CLAIMS

- 1. (Currently amended): A system for controlling transmission of data packets through an information network, comprising:
 - a Regional Transaction Processor (RTP); and
 - a Data Enabling Device (DED) operable to:

receive one or more data packets from the information network,

detect when the one or more data packets include content match information, and

issue a message to a workstation and invoke the RTP to process a transaction when the content match information is detected in the one or more data packets, wherein the DED is operable to prevent further transmission of the one or more data packets based on the content match information.

- 2. (Original): The system as set forth in claim 1, wherein the transaction processed is based on the content match information.
- 3. (Original): The system, as set forth in claim 1, wherein the DED is operable to detect when the one or more data packets include content match information at a rate proportional to the rate at which the data packets are received.
 - 4. (Canceled)
- 5. (Original): The system, as set forth in claim 1, wherein the RTP comprises a network server and a database, and is operable to process transactions for requests for content.
- 6. (Original): The system, as set forth in claim 1, wherein the DED is located at a network access point (NAP).

KOERTNER BERTANI ILI-18662 MADARTHUR BLVD SLITE 400 IRVINE, CA 93613 TEL (949) 211-0250

- 7. (Original): The system, as set forth in claim 1, further comprising a plurality of DEDs along a network route, wherein each DED is operable to communicate with at least one of the other DEDs.
- 8. (Original): The system, as set forth in claim 7, wherein the plurality of DEDs include a first DED that generates a message and one or more intermediate DEDs operable to forward the message to the DED closest to the workstation along the network route.
- 9. (Original): The system, as set forth in claim 7, wherein the plurality of DEDs are operable to communicate with each other to prevent transmitting more than one message for the same data packet through the network route.
- 10. (Original): The system, as set forth in claim 1, wherein the RTP transmits a Release_Content or Cease_Content message to the DED, based on whether the at least one data packet was authorized to be downloaded to the workstation.
- 11. (Original): The system, as set forth in claim 1, wherein the DED includes Field Programmable Gate Arrays (FPGAs).
- 12. (Original): The system, as set forth in claim 11, wherein the FPGAs can be reprogrammed over the network to perform a content matching function.
- 13. (Original): The system, as set forth in claim 11, wherein a portion of the DED can be dynamically reprogrammed and the DED is operable to continue processing the data packets during the partial reprogramming.
- 14. (Original): The system, as set forth in claim 1, further comprising a Central Storage and Backup System (CSBS) operable to communicate with the RTP, to monitor operation of the RTP, and to store transaction information.
- 15. (Original): The system, as set forth in claim 14, wherein the CSBS is operable to transmit information to reprogram the DED to communicate with another RTP.

KOKSTNER BERTANI JIV 18662 MACARI HUR BLVD SUITE 400 UKUNS, ÇA 93612 TEL (945) 231 4250

- 16. (Original): The system, as set forth in claim 1, further comprising a content matching server operable to store content match information, to communicate with the DED, and to transmit the content match information to the DED.
- 17. (Original): The system, as set forth in claim 1, wherein the DED is operable to suspend transmission of the data packets through the information network until a response to a prompt is received.
- 18. (Currently amended): A method for controlling transmission of identifiable content over an information network, comprising:

providing content match information for the content to a DED, wherein the DED is located in the information network along a transmission path of a plurality of data packets, wherein at least one data packet includes the content match information:

receiving the at least one data packet in the DED;

detecting the content match information in the at least one data packet in the DED; and issuing a prompt to a workstation based on the content match information when the content match information is detected in the at least one data packet; and preventing further transmission of the one or more data packets based on the content match information.

- 19. (Original): The method as set forth in claim 18, wherein the prompt is based on the content match information.
 - 20. (Canceled)
- 21. (Original): The method, as set forth in claim 18, further comprising: processing a transaction based on a user's response to the prompt.
- 22. (Original): The method, as set forth in claim 18, further comprising transmitting a message among a plurality of DEDs along the transmission path to prevent transmitting more than one prompt for the same data packet.

KOESTNER BERTAN'I D.A.
18663 MACARTHUR HUVIS.
SUITE 400
IRVINE, CA 92612
TEL (949) 231-0250

- 23. (Original): The method, as set forth in claim 18, further comprising: processing a transaction based on the content match information, and transmitting a Release_Content or Cease_Content message to the DED based on whether content was authorized to be downloaded to the workstation during the transaction.
- 24. (Original): The method, as set forth in claim 18, further comprising: reprogramming a portion of the DED to detect different content match information.
- 25. (Original): The method, as set forth in claim 18, further comprising suspending transmission of the at least one data packet through the information network until a response to the prompt is received.
 - 26. (Original): A computer program product comprising: program instructions to implement the method of claim 18.
 - 27. (Original): A data signal comprising: program instructions to implement the method of claim 18.
- 28. (Currently amended): An apparatus for controlling transmission of identifiable content over an information network, comprising:
 - means for providing content match information for the content to a DED, wherein the DED is located in the information network along a transmission path of a plurality of data packets, wherein at least one data packet includes the content match information;

means for receiving the at least one data packet in the DED;

- means for detecting the content match information in the at least one data packet in the DED, and
- means for issuing a prompt to a workstation based on the content match information when the content match information is detected in the at least one data packet; and
- means for transmitting a message among a plurality of DEDs along the transmission path to prevent transmitting more than one prompt for the same packet.

KUESTNER BERTANI MA 18642 MACARTHUE BLVD SUITE 400 IRVINE CA 92612 TEL (949) 311-0230

- 29. (Original): The apparatus as set forth in claim 28, further comprising means for generating the prompt based on information in the at least one data packet.
- 30. (Original): The apparatus, as set forth in claim 28, further comprising: means for preventing further transmission of the one or more data packets based on information in the at least one data packet.
- 31. (Original): The apparatus, as set forth in claim 28, further comprising: means for processing a transaction based on a user's response to the prompt.
 - 32. (Canceled)
- 33. (Original): The apparatus, as set forth in claim 28, further comprising: means for processing a transaction based on the content match information, and means for transmitting a Release_Content or Cease_Content message to the DED based on whether content was authorized to be downloaded to the workstation during the transaction.
- 34. (Original): The apparatus, as set forth in claim 28, further comprising: means for reprogramming a portion of the DED to detect different content match information.
- 35. (Original): The apparatus, as set forth in claim 28, further comprising: means for suspending transmission of the at least one data packet through the information network until a response to the prompt is received.
- 36. (Currently amended): An apparatus for controlling transmission of data packets in an information network, comprising:
 - a Regional Transaction Processor (RTP) operable to communicate with a Data Enabling Device (DED) and at least one workstation, wherein the DED is operable to detect content match information in at least one of the data packets, and further wherein the RTP comprises:

instructions operable to generate information to include in a prompt to be presented at the workstation, wherein the prompt is based on

KOESTNER BERTANI IJF 1900J MAÇAKIHUR BLVD. SUITE 400 IRVINE, CA 22612 TEL (949) 231-0250 information in the at least one data packet, wherein the DED is operable to detect the content match information at a rate proportional to the rate at which the data packets are received.

37. (Canceled)

- 38. (Original): The apparatus, as set forth in claim 36, wherein the DED is operable to prevent further transmission of one or more of the data packets based on the information in the at least one data packet.
- 39. (Original): The apparatus, as set forth in claim 36, wherein the RTP further comprises: instructions operable to process a transaction based on the information in the at least one data packet.
- 40. (Original): The apparatus, as set forth in claim 36, wherein a plurality of DEDs are positioned along a network route, and further wherein each DED is operable to communicate with at least one of the other DEDs.
- 41. (Original): The apparatus, as set forth in claim 40, wherein the plurality of DEDs include a first DED that generates a message and one or more intermediate DEDs operable to forward the message to the DED closest to the workstation along the network route.
- 42. (Original): The apparatus, as set forth in claim 40, wherein the plurality of DEDs are operable to communicate with each other to prevent transmitting more than one message for the same data packet through the network route.
- 43. (Original): The apparatus, as set forth in claim 39, wherein the RTP is further operable to transmit a Release_Content or Cease_Content message to the DED, based on whether the at least one data packet was authorized to be downloaded to the workstation during the transaction.

KOESTNER BERTANI ...

18662 MACARTHUR BLVD
9UITE 400
RIVINE EA 92012
TEL (949) 231-0260
FAX (949) 231-0260

- 44. (Original): The apparatus, as set forth in claim 36, wherein a portion of the DED can be dynamically reprogrammed and the DED is operable to continue processing packets during the partial reprogramming.
- 45. (Original): The apparatus, as set forth in claim 39, wherein the RTP is operable to communicate with a Central Storage and Backup System (CSBS), wherein the CSBS is operable to monitor operation of the RTP, and to store transaction information.
- 46. (Original): The apparatus, as set forth in claim 45, wherein the CSBS is operable to transmit information to reprogram the DED to communicate with another RTP.
- 47. (Original): The apparatus, as set forth in claim 36, wherein the RTP is operable to communicate with a content matching server, wherein the content matching server is operable to store content match information, to communicate with the DED, and to transmit the content match information to the DED.
- 48. (Original): The apparatus, as set forth in claim 36, wherein the DED is further operable to suspend transmission of the at least one data packet through the information network until a response to the prompt is received.
 - 49. (Currently amended): An apparatus comprising:
 - a Central Storage and Backup System (CSBS) operable to communicate with a plurality of Regional Transaction Processors (RTPs) and to provide backup storage for the RTPs, wherein the RTPs are operable to communicate with a Data Enabling Device (DED) and at least one workstation, wherein the DED is operable to detect content match information in at least one of a plurality of data packets packet, and to prevent further transmission of the plurality of data packets based on the content match information in the at least one data packet, and further wherein the RTP comprises:

instructions operable to generate information to include in a prompt to be presented at the workstation, wherein the prompt is based on information in the <u>plurality of data packets packet</u>.

KOGSTWAR BERTANI II. 18662 MACARTHUR BLVD. SUITE 400 IRVING, CA 92612 18L 1949 251-0250

- 50. (Original): The apparatus, as set forth in claim 49, wherein CSBS is further operable to monitor the operation of the RTPs.
- 51. (Original): The apparatus, as set forth in claim 49, wherein the CSBS stores transaction information for the RTPs.
- 52. (Original): The apparatus, as set forth in claim 49, wherein the CSBS maintains the content match information.
- 53. (Currently amended): A computer program product comprising: instructions to enable communication between a workstation, a Data Enabling Device (DED), and a Regional Transaction Processor (RTP), wherein the DED is operable to detect content match information in at least one data packet in a plurality of data packets and to prevent further transmission of the plurality of one or more data packets based on the information in the at least one data packet, and further wherein the RTP is operable to generate information to include in a prompt to be presented at the workstation, wherein the prompt is based on information in the at least one data packet.

KOESTNER BERTANI ILP 18003 MACARTINIA DLYD SUITE 400 IRVINII. CA 42012 TUI (949) 231-0250